

Program LEQ Professional - dane do obliczeń

Program LEQ Professional v. 6-2019 dla Windows

Projekt:

C:\Users\Dell\Documents\DOKUMENTY\GREEN PROJEKT\aaa - PROGRAM LEQ\Dane wsadowe LEQ\Dane v

Dane do obliczeń :

Współczynnik gruntu (całego obszaru analizy)-global G = 0.000

Temperatura otoczenia 10[°C]

Źródła punktowe

Nr	X[m]	Y[m]	z[m]	Pma	Symbol
1	836.3	566.5	7.7	77.9	w.komin
2	833.7	560.2	7.7	77.9	w.komin
3	843.1	555.9	7.7	77.9	w.komin
4	840.5	549.5	7.7	77.9	w.komin
5	849.9	545.2	7.7	77.9	w.komin
6	847.3	538.8	7.7	77.9	w.komin
7	856.7	534.5	7.7	77.9	w.komin
8	854.1	528.1	7.7	77.9	w.komin
9	805.7	553.9	7.7	77.9	w.komin
10	803.5	546.9	7.7	77.9	w.komin
11	813.2	541.9	7.7	77.9	w.komin
12	810.9	534.9	7.7	77.9	w.komin
13	820.7	529.9	7.7	77.9	w.komin
14	818.4	522.9	7.7	77.9	w.komin
15	828.1	517.9	7.7	77.9	w.komin
16	825.9	510.9	7.7	77.9	w.komin
17	831.8	564.1	1.0	95.0	agregat
18	828.5	562.4	1.0	65.7	paszoci
19	798.6	550.0	1.0	65.7	paszoci
20	813.2	525.6	1.0	65.7	paszoci
21	791.5	601.5	1.0	64.0	auto
22	795.2	595.1	1.0	64.0	auto
23	798.9	588.7	1.0	64.0	auto
24	802.6	582.4	1.0	64.0	auto
25	806.3	576.0	1.0	64.0	auto
26	810.1	569.7	1.0	73.2	sh

Źródła typu hala produkcyjna :

WSPÓŁRZĘDNE WIERZCHOŁKÓW :

Nr	X1[m]	Y1[m]	X2[m]	Y2[m]	X3[m]	Y3[m]	X4[m]	Y4[m]	h0[m]	h[m]
1	852.8	516.8	822.6	566.4	835.7	574.7	866.4	525.0	0.0	6.8
2	821.4	535.9	808.3	527.8	791.6	555.0	805.0	563.2	0.0	6.8
3	808.5	527.8	821.4	535.8	838.6	507.9	825.6	499.7	0.0	6.8

POZIOMY HAŁASU i IZOLACYJNOŚĆ PRZEGRÓD

Nr źródła A 63 125 250 500 1000 2000 4000 8000 wsp.odb.

1	sc.1	L wew	67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	42.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	42.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	42.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	42.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	28.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr źródła			A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
2	sc.1	L wew	67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	42.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	42.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	42.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	42.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	28.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr źródła			A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
3	sc.1	L wew	67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	42.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	42.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	42.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	42.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	28.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Punkty obserwacji

Nr	Symbol	X[m]	Y[m]	z[m]
1		825.0	613.4	4.0
2		753.1	597.4	4.0
3		817.2	489.6	4.0
4		776.0	465.0	4.0
5		781.1	456.0	4.0
6		853.9	502.5	4.0
7		930.3	374.2	4.0
8		974.6	370.6	4.0
9		491.3	517.0	4.0
10		970.1	776.9	4.0
11		1125.1	654.5	4.0
12		994.4	181.8	4.0
13		769.4	139.2	4.0

14	587.0	142.3	4.0
----	-------	-------	-----
